

# T - 223 - GSP-BGS

## PERFORATED BASE HANGERS

### STAINLESS STEEL WITH GALVANIZED BASE



### General description


The perforated base hangers are designed to fix efficiently insulation on concrete and any other rough surfaces.

It consists of a pin, firmly mounted on a perforated base.


Locking washers supplied in each box.

### Technical description

<b>Base</b>	Material	Galvanized steel
	Dimensions	50 x 50 mm (2" x 2")
	Thickness	0,4 mm (28 ga.)
	Perforation	44 holes, dia. 3.3 mm
<b>Shank</b>	Material	Stainless steel
	Diameter	2,7 mm (12 ga.)
	Lengths	25 to 400 mm (1"to 16")




<b>Locking washer: CL 2-30-SS</b>	Material	Stainless steel 304 spring type
	Diameter	30 mm (1 3/16")
	Thickness	0,33 mm (29 ga.)
	Edges	Bevelled




### Storage

Store in a dry place


### Application




Apply adequate adhesive to the underside of the hanger, or use rivets or screws.



Position the hanger and press until the adhesive seeps through perforations.



As soon as the strength of adherence is sufficient, impale the insulation on the hangers. Please consult your glue supplier to know about the drying time.



Secure with CL locking washers. If necessary cover the point with a protective cap.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.04.07