

# T - 242 (4) - CDF3 & CDF4 - PAP-ISOL

## WELDFASTENERS - WITH INSULATED WASHER HEAD & SHANK



### General description

The CDF3 & CDF4 - PAP-ISOL weldfasteners consist of a copper coated steel shank partly insulated and firmly crimped on a galvanized steel washer head, with an insulated underhead. The CDF3 & CDF4 - PAP-ISOL weldfasteners allow the fixing of aluminum faced insulation or wired mattresses on sheet metal such as airducts, metal beams, metal industrial equipment, etc. in a single operation.

It is recommended to use our welding equipment CDW-72 or any other welding gun with push down outside ring.



### Recommended use


Our CDF3 & CDF4 - PAP-ISOL weldfasteners are suitable for aluminum faced insulation or wired mattresses.

### Technical specification


		CDF3 & CDF4
SHANK	Material	copper coated steel
	Insulation	Heatshrunken polyolefin sleeve
WASHER HEAD	Material	galvanized steel
	Thickness	0,4 mm (28 ga.)
	Under head insulation	paper

### Sizes

TYPE	SIZES		
	A	B	C
CDF3	30 mm (1-3/16")	15 to 410 mm (3/5" to 16")	2,7 mm (12 ga.)
CDF4	38 mm (1-1/2")	15 to 410 mm (3/5" to 16")	2,7 mm (12 ga.)




### Application




Fix earth clamp of the welder to the sheet metal.  
Lay insulation on sheet metal



Place the weldfastener CDF on the magnetic head of the gun.  
Adjust the voltage according to the type and thickness of sheet metal



Press the pin through the insulation until the point meets the sheet metal and press the trigger



Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.07.26