

T - 207 - PBT-ABT

COLD SHRINKING TAPE



General description

Heavy duty self vulcanising duct sealing tapes made of an elastomeric modified butyl rubber adhesive.

Provides a strong and excellent airtight seal on metal ducts.

PBT

Polyethylene foil facing

Paper release liner

Rolls of 50 or 75mm width

ABT

Aluminium foil facing

Paper release liner

Rolls of 50 or 75mm width



Technical data

	PBT	ABT
THICKNESS	0,6 mm / 0,8 mm	0,6 mm / 0,8 mm / 1 mm
BACKING	Polyethylene 0,03 mm	Aluminium 0,04 mm
TACK	Immediately	Immediately
BONDING TIME	Maximum 24h	Maximum 24h
APPLICATION TEMPERATURE	+ 5°C / + 35°C	+ 5°C / + 35°C
ADHESION TO GALVANISED STEEL	3,6 Kg / cm	2,0 Kg / cm
TEMPERATURE RANGE	- 20°C / + 70°C	- 20°C / + 80°C
FLAMMABILITY	DIN4102 kl1 B2	DIN4102 kl1 B2
SOLIDS	100 %	100 %
USE	Inside	Inside / outside
COLOUR	Light grey	Silver

Application

Surfaces should be clean and dry, free of dust, grease, oil and any other loose matter.

When applying, cut an excess of 10 cm tape to allow overlapping. Remove the release paper.

Make an overlap over the seam.

The tape should be pressed down firmly.

Storage

The product can be stored for 2 years in dry and closed packing between +5°C and +30°C.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.01.14