

General description

The kit **square foot** is designed to support metallic structures (H-frames) on roofs or in industrial spaces. Suitable for 41 x 41 mm slotted channel rails.

- Designed to fit STRUT channel (not supplied)
- Preserves the waterproofing membrane of the roof
- Easy and fast installation
- Closed cell polyethylene anti-vibration pads pre-attached
- Great flexibility: adjustable height / weight
- Suitable for 41 x 41 mm slotted channel rails

B-SQF	B-KSF
	
<p>The square foot (B-SQF-305 & B-SQF-500) includes :</p> <ul style="list-style-type: none"> • High Density Polyethylene (HDPE) foot • Pre-attached insulating mats 	<p>The H frame kit (B-KSF - 30 & B-KSF - 50) includes :</p> <ul style="list-style-type: none"> • Square foot : x2 • M10 brackets : x2 • M10 fixings : x4

Technical specification

Material	High Density Polyethylene (HDPE)	
Dimensions	B-SQF-305	305 x 305 x 120 mm
	B-SQF-500	500 x 500 x 120 mm
Maximum load per set of 2 feet	305 x 305 : 350 Kg* / 500 x 500 : 500Kg*	
Recommended temperature	-30°C / +110°C	

* The support rails not being supplied by us, loads are given for information. Please refer to the technical data of rails to know the maximum load.

Application

Designed to support ventilation ducts, cables trays, pipes.

