

T - 46701 - CLIMA-SEAL

ACRYLIC SEALANT



General description

Acrylic water based sealant

Available in 6 kg buckets or 280 ml cartridges

Excellent adhesion to metal

Durability and flexibility

Use : airtightness on airduct



Technical specifications

BASE MATERIAL	Water based acrylic polymer
ASPECT	Malleable paste
COLOR	Grey
WEIGHT PER LITER	1,60 Kg
APPLICATION TEMPERATURE	+5°C / +40°C
OPERATING TEMPERATURE	-30 ° C / +95 ° C
DRYING TIME	Touch : 30 minutes
	Through : 4 to 6 days
REACTION TO FIRE	Wet : non flammable
	British standard : BS 476 / Part 7 class 1
	French standard : M1

Application

Application by brush or spatula on clean, dry and non-greasy surfaces and a temperature of +5 °C to +40 °C.
Read the Material Safety Datasheet

Storage

At least 12 months when stored in a dry place at temperatures between +5 °C and +30 °C in its original packaging.
Protect from frost.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.04.26