

## T - 46704

MASTIC NEOPRENE IG-657 - 5 Kg / 1 Kg / 310 ml



### General description

Neoprene sealant compound of synthetic rubbers, resins and solvents.

Available in 5 kg or 1 kg buckets and 310 ml cartridges

Excellent adhesion to metal and lightly oiled surface

Durability and flexibility

Use: Airtightness on airduct both indoor and outdoor



### Technical specifications

BASE MATERIAL	Synthetic rubbers, resins and solvents
ASPECT	malleable paste
COLOR	grey
WEIGHT PER LITER	1.17 Kg
APPLICATION TEMPERATURE	> 0 ° C
OPERATING TEMPERATURE	-25 ° C / +70 ° C
DRYING TIME	few minutes
SETTING TIME	24 to 48 h
STORAGE	6 months, dry 5 ° C to 35 ° C in primary packaging
PACKING	buckets 5 Kg and 1 Kg and cartridges 310 ml
FLAMABILITY	* Wet: Inflammable * Dry: M1

### Application

Application by brush or spatula on clean, dry and non-greasy surfaces and a temperature of 5 ° C to 35 ° C.

Read the Material Safety Datasheet

### Storage

In a dry place at temperatures between +5 ° C and +35 ° C in its original packaging.

Stored in these conditions, sealant has a maximum storage period of 6 months.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2017.04.14