T - 4930 _ FBM / CBR / CLD



General description

The quick lock hose clamps **FBM**, **CBR** and **CLD** consists of continuous serrated banding with rounded edges. They are designed to secure flexible ducts to outlets, pipes and other fittings.

- The CBR fastening band allows to create a custom made fastening clamp. The band is supplied in a dispenser with markings for easy and efficient cuts at the appropriate length to achieve a desired diameter
 - The CLD locking device is specially designed to fit the CBR band.
 Thanks to it's locking device with tilting housing and screw, it is easy to adjust at proper perimeter or length.
 - The FBM is a perforated fastening clamp up to 660mm dia. It allows an easy and quick application. It is equipped with a CLD locking device securely welded on the band.





Technical specification


	CBR - FASTENING BAND	
Material	Stainless steel 430	
Length	Roll of 30 m	
Width	9 mm	
Thickness	0,6 mm	



	CLD - LOCKING DEVICE
Frame set	Coated steel
Screw material	Coated steel
Screw head	Hexagonal, cruciform and slotted



		FBM - PREFORMED BAND
Banding	Material	Stainless steel 430
	Width	9 mm
	Thickness	0,6 mm
Locking device	Material	Coated steel
	Screw	Hexagonal, cruciform and slotted
Preformed band diameters		125, 150, 175, 225, 275, 350, 400, 550, 660



Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.