

**General description**

CLIM nylon ties are designed to secure flexible ducts to outlets, pipes and other fittings. Made of high strength nylon, they are easily and quickly installed.

- To complete the job and have a perfect result, the cut-off tensioning tool allows to tie and cut-off the excess length.
- Natural colour (NT)

**Tensioning & cutting tool - NTG :**

- High leverage tensioning tool with cut-off.

**Hanger anchor - CPNT :**

- Pure nylon without halogen.
- Suitable for 9 mm wide or smaller nylon ties.
- 10 mm outside diameter (drilling bore 8 mm).



**Technical specification**

<b>Material</b>	Nylon 66
<b>Colours</b>	NT : Natural
<b>Flamability</b>	UL 94
<b>Temperature resistance</b>	Installation : -10 °C (26 °F) to +85 °C (+185 °F)
	Operation : -40 °C (-40°F) to +85 °C (185 °F)

**Dimensions**

	<b>Suitable for Diameter (mm)</b>	<b>Length (mm)</b>	<b>Width (mm)</b>	<b>Minimum Loop Tensile (kg)</b>
<b>NT 100</b>	100	400	4,8	22
<b>NT 125</b>	125	450	7,6	55
<b>NT 175</b>	175	610	9	80
<b>NT 235</b>	235	810	9	80
<b>NT 270</b>	270	920	9	80
<b>NT 370</b>	370	1220	9	80

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.