T - 7316 _ AREL / NAREL



General description

Circular aluminium external louvre with insect screen for air supply and exhaust in ventilation systems.


Enclined aluminium blades prevent water to access the airduct.



Technical description

- · Made of moulded aluminium
- · Equiped with insect screen*
- · Round mounting collar
- AREL : Coated grey (RAL9006)
- · NAREL: Natural aluminium / can be painted

Technical specification



| | d (mm) | D (mm) | H (mm) |
|----------------|--------|--------|--------|
| AREL/NAREL 100 | 100 | 124 | 19 |
| AREL/NAREL 125 | 125 | 150 | 19 |
| AREL/NAREL 150 | 150 | 179 | 17 |
| AREL/NAREL 160 | 160 | 182 | 18 |
| AREL/NAREL 200 | 200 | 223 | 20 |
| AREL/NAREL 250 | 250 | 275 | 20 |
| AREL/NAREL 315 | 315 | 345 | 21 |
| AREL/NAREL 400 | 400 | 439 | 40 |

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

^{*}Every 3 Months the screen should be cleaned to prevent clogging. The insect screen has to be removed in mechanical ventilation when used for air supply.