

General description

The AM6 models are combined in parallel. This possibility of combining insulators produces an extensive range, of which 6 models have been standardized with differences between them of 300 to 600 kg. This detail makes them unique compared with other similar products, as they outperform them in terms of their use for the most varied momentary load values possible in a machine weighing 1 to 6 tonnes.

Description of the components :

- **Springs** are protected with epoxy-polyester resin painting, resulting in high resistance to weathering
- **Cylindrical metal bushings** which protect the outside of the spring at the ends. It furthermore incorporates a visco-elastic putty which prevents direct contact of the metal parts and promotes sound blocking.
- **Rectangular metal bases** with open lateral attachment holes to make centring of drill holes easier for attachment to the floor or structure

Dynamic behaviour of our springs & rubbers



All our antivibration springs models have been tested in European Acousticals Laboratories in order to accomplish the EU Antivibration standard regulations.

See Dynamic Behaviours results Exp n° 06/32006786




Technical specification

- Low frequency isolators very indicated for HVAC installations
- The M16 leveling screws can be supplied separately for leveling
- Color coded for ease of identification




	AM6					
	900	1200	1500	2100	2700	3300
Min. Load/kg (20mm)	570	690	858	1200	1542	1884
Max. Load/kg (35 mm)	900	1000	1500	2100	2700	3300
Color	Green	Yellow	Brown	Grey	orange	Black

Assembly




Direct assembly
System for free fitting




Assembly with leveling
System supplied with leveling screws for attachment and leveling

Application



Chillers



Air handling units